

Via Caduti della Liberazione, 57 21040 Uboldo (VA) – Italia Tel: +39 02 964121 Fax: +39 02 96412294

Web: www.eurocel.it

PRODUCT INFORMATION **EUROCEL 903 ALLUMINIO**

DESCRIPTION

Single sided aluminium foil tape with liner, thicker version of 901 aluminium tape; certified DIN 4102 B1 and classified LNE – M1.

PRODUCT DATA

| Backing | 0.050 mm dead soft aluminium foil | | |
|----------|-----------------------------------|--|--|
| Adhesive | Acrylic water based | | |
| Liner | Monosiliconized paper; white | | |

| | Unit | Value | Method |
|---------------------------------|--------|----------------------|----------|
| Total thickness (without Liner) | mm | 0.077 | PSTC 133 |
| Adhesion to steel | N/25mm | 9.5 | PSTC 101 |
| Tensile strength MD | N/25mm | 85 | PSTC 131 |
| Elongation at break | % | 7 | PSTC 131 |
| Temp. Resistance | °C | 100°C (short period) | = |

APPLICATION

This product is suitable for joining aluminium insulation panels and for conditioning plants.

| Features | Benefits | | | |
|------------------------|---|--|--|--|
| Acrylic adhesive | ✓ Good adhesion in most applications ✓ Excellent resistance to UV and ageing ✓ Good resistance to temperature | | | |
| Aluminium foil backing | ✓ Excellent moisture and vapour barrier ✓ Hand tearable ✓ Resistant in most situations ✓ Well adaptable on most of shapes ✓ Stronger than 901 Aluminium | | | |

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.