



EUROCEL ECOPACK 15

Short description:

Paper carton sealing tape for packaging

Product Data

Backing:	59 g/m ² brown or white saturated crepe paper
Adhesive:	Dry natural rubber based
Total thickness	0.105 mm
Adhesion to steel	4.25 N/25mm
Tensile strength MD	87.5 N/25mm
Elongation at break	8,5 %
Temp. Resistance	60 °C

Application

Paper carton sealing tape for standard packaging.
Printable (not in negative) or available printed up to 3 colours (30% max printable surface)*
Tape must be applied at room temperature.

Features	Benefits
Dry natural rubber based adhesive	<ul style="list-style-type: none"> ➤ Good adhesion even on different types of cardboard ➤ Good adhesion even if stored in cold temperature after closing
Saturated paper backing	<ul style="list-style-type: none"> ➤ Resistant to box shock ➤ Identifies pilferage (as damaged cartons would be recognized if resealing were attempted) ➤ Hand tearable

Product shelf life and storage: 12 months, based on the product being stored at 23°C/50% relative humidity out of direct sunlight.

**Printed rolls with length more than 50 meters: 3months of shelf life*

SICAD S.p.A., Via Caduti della Liberazione, 57 21040 Uboldo (VA) - ITALY
Tel.+39 02 96412.1; Fax +39 02 96412322 export market; Fax +39 02 96780832 domestic market;
E-mail: info@eurocel.it - www.eurocel.it - www.sicadgroup.com

This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss