

Via Caduti della Liberazione, 57 21040 Uboldo (VA) – Italia Tel: +39 02 964121 Fax: +39 02 96412294

Web: www.eurocel.it

# PRODUCT INFORMATION **EUROCEL PP 35 "S"**

#### **DESCRIPTION**

Single sided packaging tape.

#### **PRODUCT DATA**

Backing	0.035 mm BOPP film	
Adhesive	Dry natural rubber and resins; transparent, white, brown	

	Unit	Value	Method
Total thickness	mm	0.055 (white) – 0.054 (brown) – 0.053 (transparent)	PSTC 133
Adhesion to steel	N/25mm	4.5	PSTC 101
Tensile strength MD	N/25mm	125	PSTC 131
Elongation at break	%	140	PSTC 131
Temp. Resistance	°C	60°C	=

### **APPLICATION**

Standard carton sealing tape, thicker version of Eurocel PP 30"S"; available in white, brown and transparent version. Printable up to 3 colours.

Features	Benefits		
Dry natural rubber and resins adhesive	<ul> <li>✓ Good adhesion in several applications</li> <li>✓ Performing even at low temperature *</li> <li>*Suggested application at room temperature over 10°C before storing sealed items at lower temperature</li> </ul>		
BOPP backing	✓ Excellent tensile strength		

## **CONDITIONS OF USE AND CONFORMITY**

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.